

AMENDMENTS TO THE CLAIMS

Listing of Claims

The following listing of claims replaces all prior versions and listings of claims in the application.

1. (Currently amended): An internal combustion engine with at least one engine member, the engine member including:

- a combustion chamber (4) of a combustible mixture with fuel and oxidant components fitted with a compression system (9),
- an ignition system (7) of the combustible mixture by an igniter,
- sequential let-through devices for the fuel and oxidant components and for the combustion products,

~~characterised in that~~ wherein

the ignition system includes a closed head (6)(12a) substantially spherical with a wall enclosing the igniter in a precombustion chamber (1), the head including a set of orifices (5) intended to communicate the combustion chamber and the precombustion chamber so that combustible mixture may flow into the precombustion chamber,

and ~~in that~~ at least one of the let-through devices is a direct injector (8) in the combustion chamber for the fuel and/or oxidant components, in all or in part, the fuel being injected directly and exclusively in the combustion chamber.

2. (Currently amended): An engine according to claim 1, ~~characterised in that~~ wherein at least one orifice (5) has dimensions of passageway letting through a flame front from the precombustion chamber (1) to the combustion chamber.

3. (Currently amended): An engine according to ~~claim 1 or 2~~, ~~characterised in that~~ claim 1, wherein at least one orifice (5b) has dimensions of passageway not letting through a flame front from the precombustion chamber to the combustion chamber while letting through unstable species resulting from the combustion in the precombustion chamber in order to enable self-ignition of the combustible mixture of the combustion chamber.

4. (Currently amended): An engine according to claim 3, ~~characterised in that~~ wherein the set of orifices have dimensions of passageway not letting through the flame front from the precombustion chamber to the combustion chamber while letting through unstable species.

5. (Currently amended): An engine according to ~~claim 3 or 4, characterised in that~~ claim 3, wherein each orifice not letting through the flame front has a diameter smaller than 1 mm.

6. (Currently amended): An engine according to ~~one of the claims 3, 4 or 5, characterised in that~~ claim 3, wherein each orifice has a length smaller than its diameter.

7. (Currently amended): An engine according to ~~any of the previous claims, characterised in that~~ claim 1, wherein the separation wall of the head (12a) between the precombustion chamber (1) and the combustion chamber (4) is made of a material with thermal conductivity greater than 10 W/K/m.

8. (Currently amended): An engine according to ~~any of the previous claims, characterised in that~~ claim 1, wherein the separation wall of the head (12a) between the precombustion chamber and the combustion chamber is made of high conductivity copper alloy (CuCr1Zr).

9. (Currently amended): An engine according to ~~any of the previous claims, characterised in that~~ claim 1, wherein the orifices of the head are minimum three in number.

10. (Currently amended): An engine according to ~~any of the previous claims, characterised in that~~ claim 1, wherein the compression system is a piston (9) in a cylindrical combustion chamber (4) with central axis, the injector (8) being arranged substantially axially opposite the piston and the ignition system (7) laterally with respect to the injector, and ~~in that~~ the orifices are predominantly arranged axially to ensure homogeneity of the combustion of the combustible mixture substantially in the whole combustion chamber.

11. (Currently amended): An engine according to ~~any of the claims 1 to 9, characterised in that~~ claim 1, wherein the compression system is a piston (9) in a cylindrical combustion chamber (4) with central axis, the ignition system (7) being arranged substantially axially opposite the

piston of the injector laterally with respect to the ignition system, and ~~in that~~ the orifices are distributed regularly on the surface of the head to ensure homogeneity of the combustion of the combustible mixture substantially in the whole combustion chamber.

12. (Currently amended): An engine according to ~~any of the claims 1 to 9, characterised in that~~ claim 1, wherein the compression system is a piston (9) in a cylindrical combustion chamber (4) with central axis, the injector (8) and the ignition system (7) being arranged laterally with respect to said axis, and ~~in that~~ the orifices are predominantly arranged axially to ensure homogeneity of the combustion of the combustible mixture substantially in the whole combustion chamber.

13. (Currently amended): An engine according to ~~any of the previous claims, characterised in that~~ claim 1, wherein the head (6) is arranged on a portion of the path of the fuel components injected so that said head may be wetted by said fuel components during the direct injection thereof.

14. (Currently amended): An engine according to ~~any of the previous claims, characterised in that~~ claim 1, wherein the ignition system with its head are a single component which replaces a traditional sparking plug and which does not require any modification of the passageway of cylinder head.

15. (Currently amended): An engine according to ~~any of the previous claims, characterised in that~~ claim 1, wherein the fuel is exclusively liquid, notably petrol.

16. (Currently amended): A method of ignition of an internal combustion engine having at least one engine member, the engine member including:

- a combustion chamber (4) of a combustible mixture with fuel and oxidant components fitted with a compression system (9),
- an ignition system (7) of the combustible mixture by an igniter,
- sequential let-through devices for the fuel and oxidant components and for the combustion products,

~~characterised in that~~ wherein

one implements an ignition system including a closed head (6a), (12) substantially spherical with a wall enclosing the igniter in a precombustion chamber (1), the head including a set of orifices (5) intended to communicate the combustion chamber and the precombustion chamber so that combustible mixture may flow into the precombustion chamber,
and in that

one introduces directly in the combustion chamber the fuel and/or oxidant components, in all or in part, through one of the let-through devices which is a direct injector (8), the fuel being injected directly and exclusively in the combustion chamber,

one introduces moreover at least some oxidant components in said combustion chamber in order to form the combustible mixture,

one causes an ignition of the combustible mixture in the precombustion chamber by the igniter, the orifices of the precombustion chamber enabling the ignition of the combustible mixture of the combustion chamber.

17. (Currently amended): A method according to ~~claim 16 characterised in that~~ claim 16, wherein one lets through the orifices some unstable species resulting from the combustion in the precombustion chamber in order to enable self-ignition of the combustible mixture of the combustion chamber without however letting through the flame front from the precombustion chamber to the combustion chamber.

18. (Currently amended): ~~An application of the A method according to claim 16 to the engine of any of the claims 1 to 15~~ claim 16, wherein the engine is an internal combustion engine with at least one engine member, the engine member including:

- a combustion chamber of a combustible mixture with fuel and oxidant components fitted with a compression system,
- an ignition system of the combustible mixture by an igniter,
- sequential let-through devices for the fuel and oxidant components and for the combustion products,

wherein

the ignition system includes a closed head substantially spherical with a wall enclosing the igniter in a precombustion chamber, the head including a set of orifices intended to communicate the

Preliminary Amendment
Attorney Docket No. 052472

combustion chamber and the precombustion chamber so that combustible mixture may flow into the precombustion chamber,

and at least one of the let-through devices is a direct injector in the combustion chamber for the fuel and/or oxidant components, in all or in part, the fuel being injected directly and exclusively in the combustion chamber.